

Bermocoll® 产品线

涂料级别	产品名称	粘度 (mPa·s)*	
		1% 溶液	2% 溶液
常规型	Bermocoll E 230 FQ		260 – 360
	Bermocoll E 320 FQ		1850 – 2650
	Bermocoll EM 7000 FQ	6000 – 8000	
生物稳定型	Bermocoll EBS 351 FQ		5000 – 6000
	Bermocoll EBS 451 FQ	3000 – 4000	
	Bermocoll EBS 481 FQ	4000 – 6000	
	Bermocoll EBM 3000	2000 – 3000	
	Bermocoll EBM 3500	2500 – 3500	
	Bermocoll EBM 5500	5000 – 6500	
	Bermocoll EBM 8000	7000 – 9000	
	Bermocoll EBM 8500	7500 – 9000	
	Bermocoll EBM 10000	10000 – 15000	
高性能型	Bermocoll Prime 1000	500 – 900	
	Bermocoll Prime 1500	900 – 1500	
	Bermocoll Prime 2500	2200 – 3200	
	Bermocoll Prime 3500	3000 – 4000	
缔合型	Bermocoll EHM 200	350 – 700	
	Bermocoll EHM 300	1700 – 3000	
	Bermocoll EHM 500	7000 – 10000	
高性能缔合型	Bermocoll EHM EXTRA	250 – 450	
	Bermocoll Flow		500 – 1500
Bermocell	Bermocell 25K2	3000 – 4000	
	Bermocell 100K2	>10000	

* 粘度测试方法：在 20°C (68°F) 的水溶液中使用 Brookfield LV 粘度计，测试转速设定为 12 rpm。