

Redicote® C-500-1

Emulsifier for cationic quick-set bitumen emulsions for quick-traffic slurry and micro surfacing

Benefits and features

- Dependable cohesion development
 Emulsions formulated with Redicote C-500 1 provide mixtures showing good cohesion development with a wide range of aggregate types and weather conditions while providing sufficient mix times
- High reactive aggregates
 Cationic quick-set emulsions made with
 Redicote C-500-1 provide mix time even with
 reactive aggregates and in hot weather
- Low and medium reactive aggregates

 The product can be used also with aggregates of low or moderate reactivity
- Combined systems
 The product can be used together with
 Redicote C-471 to provide economical emulsion
 recipes suitable for a wide range of conditions

Storage and handling

Redicote C-500-1 may be stored in carbon steel tanks. Bulk storage should be maintained at 45-65°C (113-149°F). Avoid extended heating above 65°C (150°F). Protect against exposure to moisture. Redicote C-500-1 contains amines and may cause severe irritation or burns to skin and eyes. Protective gloves and safety goggles must be worn when handling this product.

For further information consult the Safety Data Sheet.

Packaging information

Redicote C-500-1 is available in tight head steel drums of 400 lbs (181 kg) net weight.

Dosage

Cationic quick set emulsion 0.7-2.0% pH 1-3 hydrochloric acid

Specification

Amine value, mg KOH/g	370-410	SMA CL002
Water, %	max 1	SMA CL007

Physical properties

Appearance at 25°C	viscous liquid				
Flash point, °C	>200 (>392°F)				
Pour point, °C	5 (41°F)				
		20	30	40	$^{\circ}C$
		68	86	104	°F
Density, g/cc		0.98	0.97	0.96	_
Density, lbs/U.S. gal		8.12	8.08	8.03	_
Viscosity, mPa.s (cP)		46100	17700	6800	_

Physical properties are typical data based on our own measurements or derived from the literature. They do not constitute part of the delivery specification.

Notes

For regulatory reasons this product is not available within the EU, USA, Canada and China.

Contact us directly for detailed product information and sample request website | nouryon.com/markets/asphalt email | asphalt@nouryon.com

Nouryon

Nouryon is a global, specialty chemicals leader. Markets and consumers worldwide rely on our essential solutions to manufacture everyday products, such as personal care, cleaning goods, paints and coatings, agriculture and food, pharmaceuticals, and building products. Furthermore, the dedication of more than 7,900 employees with a shared commitment to our customers, business growth, safety, sustainability and innovation has resulted in a consistently strong financial performance. We operate in over 80 countries around the world with a portfolio of industry-leading brands. Visit our website and follow us @Nouryon and on LinkedIn.

All information concerning our products and/or all suggestions for handling and use contained herein (including formulation and toxicity information) are offered in good faith and are believed to be reliable. However, Nouryon makes no warranty express or implied (i) as to the accuracy or sufficiency of such information and/or suggestions, (ii) as to any product's merchantability or fitness for a particular use or (iii) that any suggested use (including use in any formulation) will not infringe any patent. Nothing contained herein shall be construed as granting or extending any license under any patent. The user must determine for itself by preliminary tests or otherwise the suitability of any product and of any information contained herein (including but not limited to formulation and toxicity information) for the user's purpose. The safety of any formulations described herein has not been established. The suitability and safety of a formulation should be confirmed in all respects by the user prior to use. The information contained herein supersedes all previously issued bulletins on the subject matter covered.

Products mentioned are trademarks of Nouryon and registered in many countries.

nouryon.com